TECHNICAL DATA

Fluke TL26A 60 in. 5-Way Test Lead Set



Product overview: Fluke TL26A 60 in. 5-Way Test Lead Set

5 ways to connect:

1. U-shaped nose for blade-shaped terminals
2. Notched jaw for gripping screw heads, bare wire or terminals
3. Serrated teeth for gripping threaded or wire-wrapped terminals
4. Cluster of sharp needles for piercing small gauge (#22-#28 AWG) wires
5. Large piercing needle for penetrating larger gauge wires

Ordering information



Fluke TL26A

Part#: 1273172

UPC#: 095969083546

- 60" (1.5m), silicone-insulated leads
- Useable from -20 °C to +55 °C (-4 °F to +131 °F)
- Maximum voltage: 30 V AC, 60 V DC
- Maximum current: 8 A

Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2026 Fluke Corporation.
Specifications subject to change without notice.
10/2026

Modification of this document is not permitted without written permission from Fluke Corporation.